



Quantifying the Dependence of Changes in Instrument Calibration on Reflected Solar Satellite Cloud Retrievals

Yolanda Roberts¹, Bruce Wielicki¹, Sunny Sun-Mack², Pat Minnis¹, Lusheng Liang², Larry Di Girolamo³

¹NASA Langley Research Center, Hampton, VA ²Science Systems and Applications, Inc. (SSAI), Hampton, VA ³University of Illinois at Urbana-Champaign






Climate Absolute Radiance Refractivity Observatory

- NASA's CLARREO will provide the first *SI traceable* high accuracy spectral measurements of the reflected shortwave and emitted longwave *to detect* changes in Earth's climate
- CLARREO Intercalibration with other sensors will enable climate change observations of several variables
 - E.g. temperature & water vapor profiles, cloud properties, broadband radiation, ocean & land surface properties
- High absolute accuracy necessary for climate change observations
 - For rigorous climate model testing, reliable climate model predictions, and the resulting policy decisions.

How do we ensure to design these instruments with the accuracy required to observe changes in the climate system?







CLARREO to be a Calibration Standard In-Orbit



- CLARREO Intercalibration with potentially up to 40 other LEO and GEO sensors would enable climate change observations of several variables
 - E.g. temperature & water vapor profiles, cloud properties, broadband radiation, ocean & land surface properties








Determining the Accuracy of Decadal Trends



The accuracy of a perfect climate observing system is limited by the natural variability of the climate system [Leroy et al., 2008].




Variable Trend Uncertainty is Dependent Upon:

- Magnitude of natural variability
- How long trend is observed
- Climate Observing System Accuracy

CLARREO BAMS Article [Wielicki et al., 2013]





Determining Necessary Instrument Accuracy



Accuracy Uncertainty Factor

$$U_a = \sqrt{1 + \frac{\sigma_{Vcal}^2 \tau_{cal}}{\sigma_{var}^2 \tau_{var}}} = \frac{\text{Variable Trend Uncertainty for } \textbf{Actual Instrument}}{\text{Variable Trend Uncertainty for } \textbf{Perfect Instrument}}$$

Calculate natural variability terms from annually and globally (60S-60N) averaged cloud property time series

- σ_{Var} : Standard deviation
- τ_{Var} : Time between independent measurements dependent on the lag-1 autocorrelation

For an instrument 20% from perfect -----

Estimated instrument lifetime used as calibration autocorrelation time

$$\rightarrow$$
 $\tau_{cal} = 5 \text{ Years}$




Determining Necessary Instrument Accuracy



From the accuracy uncertainty ratio, we get the calibration uncertainty as a function of the cloud property in question.


$$U_a = \sqrt{1 + \frac{\sigma_{Vcal}^2 \tau_{cal}}{\sigma_{var}^2 \tau_{var}}}$$

We need the sensitivity of retrieved cloud property to changes in instrument calibration.



Δ Instrument Calibration (Reflectance or Brightness Temperature)


$$\frac{\partial(\text{Cloud Property})}{\partial(\text{Instrument Calibration}_{\lambda})}$$




Sensitivity of $log(\tau_c)$ to Calibration Changes




CERES-MODIS algorithm primarily uses 0.65 μ m MODIS Reflectance to retrieve Cloud Optical Thickness (τ_c)






Trend Uncertainty of $log(\tau_c)$









Trend Uncertainty of $log(\tau_c)$



0.65 μm Calibration Uncertainty (95% Confidence)









Sensitivity of $log(\tau_c)$ to Calibration Changes



CERES-MODIS algorithm primarily uses 0.65 μ m MODIS Reflectance to retrieve Cloud Optical Thickness (τ_c)







Impact of Clear-Sky Updating on 0.65µm Sensitivity



Sensitivity between calibration changes and variable change with and without clear-sky updating.






Impact of Clear-Sky Updating on 0.65µm Sensitivity



Sensitivity between calibration changes and variable change with and without clear-sky updating.







Sensitivity of Cloud T_{eff} to Calibration Changes




CERES CPRS primarily uses 11 µm MODIS Brightness Temperature to retrieve Cloud Effective Temperature





Trend Accuracy of Cloud Effective Temperature 🛰 🦠









Sensitivity of Cloud T_{eff} to Calibration Changes



CERES CPRS primarily uses 11 µm MODIS Brightness Temperature to retrieve Cloud Effective Temperature





Next Steps: Cloud Property Accuracy Studies



- Accuracy Uncertainty Ratio rigorous and universal method to determine observing system accuracy requirement & time to detect trends
- Further investigating CLARREO requirements based on natural variability of cloud properties
- These results depend on cloud retrieval algorithm (MODIS, CERES/MODIS, VIIRS, etc)
- Thus far we have investigated the requirements based on changes in individual MODIS wavelength bands.
 - Next Step: Determine requirements based on changes in multiple bands
- Next Steps: Are the biases in cloud retrievals due to algorithm assumptions stable over climate scales?
 - Starting Point: Quantifying how much the 3D Optical Depth Bias changes over multiple decades?